



OEM-XD-635/5-8W



**OEM RED DIODE LASER  
AT 635nm**

OEM red diode laser at 635nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	635±5
Operating mode	CW
Output power (mW)	>5000, 6000, ..., 8000
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Polarization direction	Horizontal+ Vertical
Beam diameter at the aperture (mm)	~7×5.5
Beam divergence, full angle (mrad)	<1.6×2.6
Warm-up time (minutes)	<5
Beam height from base plate (mm)	35
Operating temperature (°C)	25+/-3
Driver (12VDC 15A)	PSU-PN7-OEM/ PSU-PN7-OEM-H
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional
Expected lifetime (hours)	10000
Warranty	1 year



OEM-XD-635	PSU-PN7-OEM	PSU-PN7-OEM-H	Accessory (Power supply 100-240VAC)
<p>200(L)×150(W)×61(H) mm<sup>3</sup>, 4.5kg</p>	<p>120(L)×65(W)×29(H) mm<sup>3</sup>, 0.3kg</p>	<p>140(L)×80(W)×67(H) mm<sup>3</sup>, 0.6kg</p>	<p>177.5(L)×62(W)×30(H) mm<sup>3</sup>, 0.5kg</p>