



MDL-SD-520/2W



GREEN DIODE LASER
AT 520nm

Green diode laser at 520nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	520±5
Operating mode	CW
Output power (mW)	2000
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Polarization direction	Horizontal/ Vertical
Beam diameter at the aperture (1/e ² ,mm)	~2.6×2.5
Beam divergence, full angle (mrad)	<1.2×0.4
Warm-up time (minutes)	<5
Beam height from base plate (mm)	68.5
Operating temperature (°C)	10~35
Power supply (100-240VAC)	PSU-H-LED/ PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional
Expected lifetime (hours)	10000
Warranty	1 year



MDL-SD-520	PSU-H-LED	PSU-H-FDA
<p>131.2(L)×99(W)×91(H) mm³, 1.6kg</p>	<p>277 (L) ×145(W) ×106(H) mm³, 2.3kg</p>	<p>275 (L) ×145(W) ×104(H) mm³, 2.1kg</p>