

MDL-XS-405/1~200mW



### DIODE XS SERIES LASER AT 405nm


Diode XS series laser module at 405nm, features with integrated electronics, plug and play, miniaturization, standardization of interface advantages of continuous diode lasers. It is the ideal solution for a wide range of applications including life sciences, environmental monitoring, inspection and machine vision.



#### SPECIFICATIONS

Wavelength (nm)	405±5
Operating mode	CW
Output power (mW)	>1, 10, 20, ..., 200
Power stability (rms, over 4 hours)	<1%, <3%
Transverse mode	Near TEM <sub>00</sub>
Noise of amplitude(rms,20Hz~20MHz)	<1%(<0.5%, optional)
M <sup>2</sup> factor	<1.2
Beam diameter at the aperture (1/e <sup>2</sup> ,mm)	~1.0
Beam divergence, full angle (mrad)	<1.0
Polarization ratio	>50:1 (>100:1, optional) Horizontal ±5 degree (Vertical Optional)
Warm-up time (minutes)	<5
Beam height from base plate (mm)	19
Operating temperature (°C)	10~35
Input voltage	+12VDC
Modulation options	DMOD (TTL) or AMOD (Analog) up to 1MHz DMOD+AMOD (TTL + Analog)
Expected lifetime (hours)	10000
Warranty	1 year

Note: The laser head needs to be used on a heat sink with good heat dissipation.



MDL-XS-405	Optional Power Supply
<p>79.1(L) ×40(W) ×64 (H) mm<sup>3</sup>, 0.2kg</p>	<p>121(L) ×50(W) ×30.8 (H) mm<sup>3</sup>, 0.3kg</p>

Kokyō

株式会社光饗

<http://www.symphotony.com/> メール : info@symphotony.com