



TEM-F-520/1~20mW ( $TEM_{00}$ )

### GREEN DIODE LASER AT 520nm

Green diode laser module at 520nm is made features of  $TEM_{00}$  mode, ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc



#### SPECIFICATIONS

Wavelength (nm)	520±5
Output power (mW)	>1,2,3..... 20
Transverse mode	$TEM_{00}$
Operating mode	CW
Ellipticity	>0.98
Beam quality ( $M^2$ )	<1.1
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Pointing stability after warm-up (mrad)	<0.05
Polarization ratio	no fixed polarization
	>50:1 (>100:1 optional)
Warm-up time (minutes)	<5
Beam divergence, full angle (mrad)	<1.0
Beam diameter at the aperture (mm)	~1.0
Beam height from base plate (mm)	25
Operating temperature (°C)	10~35
Power supply (90~264VAC)	PSU-III-LED
	PSU-III-FDA
Modulation option	TTL/Analog 1Hz~5KHz, 1Hz~10KHz, 1Hz~30KHz, and TTL on/off
Expected lifetime (hours)	10000
Warranty period	1 year



Kokyo

株式会社光響

<http://www.symphotony.com/> メール : info@symphotony.com