

MDL-XD-660/4-5W



RED DIODE LASER
AT 660nm

Red diode laser at 660nm red laser is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc. It's easy to be installed in customer's equipment.



SPECIFICATIONS

Wavelength (nm)	660±5
Operating mode	CW
Output power (mW)	>4000, 4100, 4200, ..., 5000
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Polarization direction	Horizontal/ Vertical
Beam diameter at the aperture (mm)	~9.5×14
Beam divergence, full angle (mrad)	<3.5×4.0
Warm-up time (minutes)	<5
Beam height from base plate (mm)	89
Operating temperature (°C)	10-35
Power supply (100-240VAC)	PSU-N-LED/ PSU-N-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional
Expected lifetime (hours)	10000
Warranty	1 year



MDL-XD-660	PSU-N-LED	PSU-N-FDA
<p>226(L)×150(W)×115(H) mm³, 6.6 kg</p>	<p>307(L)×150(W)×106(H) mm³, 3.0kg</p>	<p>307(L)×150(W)×106(H) mm³, 3.0kg</p>