



MLL-III-660L/1~180mW



LOW NOISE RED DIODE LASER AT 660nm

Low noise red diode laser at 660nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	660±5
Operating mode	CW
Output power (mW)	>1,10,20,...,180
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	Near TEM ₀₀
Noise of amplitude (rms, 20Hz~20MHz)	<1%
M ² factor	<1.5 (<1.2, optional)
Beam diameter at the aperture (1/e ² ,mm)	~3.0 (~1.2, optional)
Beam divergence, full angle (mrad)	<1.0
Polarization ratio	>50:1 (>100:1, optional) Horizontal±5 degree (Vertical Optional)
Warm-up time (minutes)	<5
Pointing stability after warm-up (mrad)	<0.05
Beam height from base plate (mm)	24.8
Operating temperature (°C)	10~35
Power supply (85~264VAC)	PSU-III-LED/ PSU-III-FDA
TTL / Analog modulation	TTL or Analog with 1Hz~1KHz 1KHz~10KHz, 10KHz~30KHz optional
Expected lifetime (hours)	10000
Warranty	1 year



MxL-III-660L	PSU-III-LED	PSU-III-FDA
<p>143.5(L) × 73(W) × 46.2(H) mm³, 0.7kg</p>	<p>188.6 (L) × 155(W) × 92 (H) mm³, 1.5kg</p>	<p>171(L) × 130(W) × 62.2 (H) mm³, 1.2kg</p>

Kokyō

株式会社光饗

<http://www.symphotony.com/> メール : info@symphotony.com