



MRL-I-650/655/1~1000mW

RED DIODE LASER
At 650/655nm

Red diode laser at 650/655nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is used in measurement, lighting show, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	650±10/ 655±10	
Operating mode	CW	
Output power (mW)	>1, 100, 200, ..., 1000	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Transverse mode	Multimode	
Dimensions of beam at the aperture (mm)	~5×8	
Beam divergence, full angle (mrad)	<2.5	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply (85-264VAC)	PSU-III-LED	PSU-III-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	



MxL-I-650/655	PSU-III-LED	PSU-III-FDA
<p>140 (L) ×36(W) ×40.2 (H) mm³, 0.3kg</p>	<p>188.6 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	<p>171(L) ×130(W) ×62.2 (H) mm³, 1.2kg</p>