



MRL-III-635R/1~150mW



RED DIODE LASER  
AT 635nm

Red diode laser at 635nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	635±10
Operating mode	CW
Output power (mW)	>1,10,50,..., 150
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	Round
Beam diameter at the aperture (mm)	~2
Beam divergence, full angle (mrad)	<18
Warm-up time (minutes)	<5
Beam height from base plate (mm)	24.8
Operating temperature (°C)	10~35
Power supply (85-264VAC)	PSU-III-LED/ PSU-III-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional
Expected lifetime (hours)	10000
Warranty	1 year



MxL-III-635R	PSU-III-LED	PSU-III-FDA
<p>143.5(L)×73(W)×46.2(H) mm<sup>3</sup>, 0.7kg</p>	<p>188.6 (L) ×155(W) ×92 (H) mm<sup>3</sup>, 1.5kg</p>	<p>171(L) ×130(W) ×62.2 (H) mm<sup>3</sup>, 1.2kg</p>