


HPL-1064-QM/100~300W

**WATER COOLING LD PUMPED  
ALL-SOLID-STATE Q-SWITCHED  
INFRARED LASER at 1064nm**

All solid state AOM Q-switched infrared laser at 1064nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, science research, military, and so on.



SPECIFICATIONS		
Wavelength (nm)	1064±1	
Operating mode	Acousto-Optics Q-switched	
Average power (W)	200	300
Pulse duration (ns)	~150 @10kHz&200W	~300 @10kHz&300W
Rep. rate (kHz)	10~20 (It is possible to customize other repetition rates )	
Single pulse energy (mJ)	20 @10kHz&200W	30 @10kHz&300W
Peak power (kW)	200 @10kHz&200W	300 @10kHz&300W
Ave power stability (over 4 hours)	<3%, <5%	
Beam divergence, full angle (mrad)	<3.5	
Beam diameter at the aperture (mm)	≥12	≥15
Beam height from base plate (mm)	55	
Warm-up time (minutes)	<10	
Cooled method	Water Cooled	
Operating temperature (°C)	15~35	
Power supply (220/110VAC)	PSU-HPL (2U×2)	
Expected lifetime (hours)	10000	
Warranty period	1 year	
Pilot light (optional)	5mW @650nm(optional)	



HPL-1064-QM	PSU-HPL-Q (2U)	PSU-HPL-CW (2U)	Water Chiller
<p>437(L)×188(W)×116(H) mm<sup>3</sup>, 15kg (200W)</p>	<p>380(L) x 485(W) x 90(H) mm<sup>3</sup>, 7.5kg</p>	<p>288(L) x 482(W) x 90(H) mm<sup>3</sup>, 5.5kg</p>	<p>475 (L)×575(W)×805(H) mm<sup>3</sup>, 71kg (200W) 505 (L)×625(W)×905(H) mm<sup>3</sup>, 95kg (&gt;200W)</p>