

MDL-E-980/1~30mW



NARROW LINewidth DIODE LASER AT 980nm

Narrow linewidth diode laser module at 980nm is made features of narrow spectral linewidth, stable wavelength, long lifetime and easy operating, which is widely used in precision measurement, high resolution spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	980±10
Operating mode	CW
Output power (mW)	>1, 2, 3, ..., 30
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	Near TEM ₀₀
Spectral linewidth (nm)	<0.06, <0.03(extra heatsink)
M ² factor	<1.5
Beam diameter at the aperture (1/e ² , mm)	~3.5
Beam divergence, full angle (mrad)	<1.0
Polarization ratio	>50:1 (>100:1, optional) Horizontal ±5 degree (Vertical Optional)
Warm-up time (minutes)	<15
Beam height from base plate (mm)	30
Operating temperature (°C)	20~30
Power supply (85-264VAC)	PSU-III-FDA
Expected lifetime (hours)	10000
Warranty	1 year



MDL-E-980	PSU-III-FDA
 122.5(L) ×65(W) ×50 (H) mm ³ , 1.0kg	 171(L) ×130(W) ×62.2 (H) mm ³ , 1.2kg

Kokyo

株式会社光響

<http://www.symphotony.com/> メール : info@symphotony.com