



MDL-H-665/800~2000mW



**RED DIODE LASER  
At 665nm**

Red diode laser module at 665nm is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



**SPECIFICATIONS**

Wavelength (nm)	665±5	
Operating mode	CW	
Output power (mW)	>800, 900, 1000, ..., 2000	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Transverse mode	Multimode	
Beam diameter at the aperture (mm)	~5×8	
Beam divergence, full angle (mrad)	<3.0	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	29	
Operating temperature (°C)	10~35	
Power supply (100-240VAC)	PSU-H-LED	PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	



MxL-H-665	PSU-H-LED	PSU-H-FDA
<p>160 (L) × 77(W) × 60 (H) mm<sup>3</sup>, 0.9kg</p>	<p>277 (L) × 145(W) × 106(H) mm<sup>3</sup>, 2.3kg</p>	<p>275 (L) × 145(W) × 104(H) mm<sup>3</sup>, 2.1kg</p>