



MIL-III-1444/1~400mW

**LD PUMPED ALL-SOLID-STATE
INFRARED LASER AT 1444nm**

All solid state infrared laser is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, measurement, optical instrument, optical sensor, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1444 ± 2		
Output power (mW)	>1, 5, 10, 20, ... , 400		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%, <10%		
Warm-up time (minutes)	<10		
M ² factor	<1.5		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at 1/e ² (mm)	~1.5		
Beam height from base plate (mm)	24.8		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option		
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-1444	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
<p style="text-align: center;">140.8(L)×73(W)×46.2(H) mm³, 0.6kg</p>	<p style="text-align: center;">153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	<p style="text-align: center;">133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	<p style="text-align: center;">100 (L) ×62(W) ×56 (H) mm³, 0.2kg</p>