



MRL-FN-721 /1~500mW



LD PUMPED ALL-SOLID-STATE RED LASER AT 721nm

DPSS red laser at 721nm is made features of ultra compact, long lifetime, high stability and easy operating, which is widely used in measurement, spectrum analysis, and scientific research etc.



SPECIFICATIONS

Wavelength (nm)	721±1
Operating mode	CW
Output power (mW)	>1, 10, 20, ... ,500
Power stability (rms, over 4 hours)	<5%, <10%
Transverse mode	TEM ₀₀
M ² factor	<1.2
Dimensions of beam at the aperture (mm)	~2.0
Beam divergence, full angle (mrad)	<1.5
Polarization ratio	>100:1 (Vertical)
Warm-up time (minutes)	<10
Beam height from base plate (mm)	27.4
Operating temperature (°C)	10~35
Power supply (90-264VAC or 5VDC)	PSU-H-LED PSU-H-FDA
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option
Expected lifetime (hours)	10000
Warranty	1 year



MXL-FN-721	PSU-H-LED	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 1.36 kg</p>	<p>277 (L) × 145 (W) × 106 (H) mm³, 2.6 kg</p>	<p>236(L) × 145(W) × 104(H) mm³, 2.3 kg</p>