



PS-Seed-1064/1~300mW


PS pulsed 1064nm laser

Picosecond pulsed laser at 1064 nm with SESAM technique is made features of pulse width less than 20 ps picosecond, compact design and long lifetime, which is widely used in laser seed source, nonlinear optics, spectrum analysis, the photonic crystal micro processing, optical film micro processing



SPECIFICATIONS

Wavelength (nm)	1064±1nm
Operating mode	Mode-locked
Output power	@Mode-locked mode 1~300mW
Ave power stability (over 4 hours)	<1%, <3%
Transverse mode	TEM ₀₀
Pulse duration (ps)	10~20
Rep. rate (MHz)	80
Polarization ratio	>100:1
M ² factor	1.2
Beam divergence, full angle (mrad)	<2.0
Beam diameter at the aperture (1/e ² ,mm)	~2
Beam height from base plate (mm)	48
Warm-up time (minutes)	<10
Operating temperature (°C)	10~30
Power supply (90-264VAC)	PSU-Z-LED
Expected lifetime (hours)	10000
Warranty period	1 year



PS-Seed-1064	PSU-Z-LED
<p>491(L) × 214(W) × 80(H) mm³, 14kg</p>	<p>320(L) × 300(W) × 123(H) mm³, 6.2 kg</p>