



MLL-FN-532/400~2500mW



**LD PUMPED ALL-SOLID-STATE  
LOW NOISE GREEN LASER  
AT 532nm**

Low noise all solid state 532nm green laser is made features of high output power stability, good beam profile, ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.



SPECIFICATIONS

Wavelength (nm)	532±1	
Operating mode	CW	
Output power (mW)	>400,500, ... , 1500	>1500,1600, ... , 2500
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%, <5%
Transverse mode	TEM <sub>00</sub>	
Spectral linewidth (nm)	<0.1 (< 0.003 Optional)	<0.1
Noise of amplitude (rms, 20Hz~20MHz)	<0.5%, <1%	
M <sup>2</sup> factor	<1.2(<1.1 optional)	
Beam diameter at the aperture (1/e <sup>2</sup> , mm)	~2.0	
Beam divergence, full angle (mrad)	<1.5	
Beam height from base plate (mm)	27.4	
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MLL-FN-532	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm<sup>3</sup>, 1.5 kg</p>	<p>275(L)×145(W)×104(H) mm<sup>3</sup>, 2.3 kg</p>