



MSL-DS-532/1~100mW

### SINGLE LONGITUDINAL MODE GREEN LASER AT 532 nm

All solid state single longitudinal mode green laser at 532 nm is made features of ultra compact, small size, photoelectric integrated, built-in electric shutter, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, brillouin scattering, physics experiment, etc.



#### SPECIFICATIONS

|  |                                  |
|--|----------------------------------|
| Model  | MSL-DS-532                       |
| Wavelength (nm)                                      | 532±1                            |
| Operating mode                                       | CW                               |
| Output power before fiber (mW)                       | >1,5,10,20,...,100               |
| Power stability (rms, over 4 hours)                  | <1%,<2%,<3%                      |
| Transverse mode                                      | TEM <sub>00</sub>                |
| Longitudinal mode                                    | Single                           |
| Spectral linewidth (nm)                              | <0.00001                         |
| Coherent length (m)                                  | >50                              |
| Noise of amplitude (rms, 20Hz~20MHz)                 | <0.5%                            |
| M <sup>2</sup> factor                                | <1.2(<1.1 optional)              |
| Beam diameter at the aperture( 1/e <sup>2</sup> ,mm) | 0.7±0.05                         |
| Beam divergence, full angle (mrad)                   | <1.5                             |
| Pointing stability after warm-up (mrad)              | <0.05                            |
| Pointing stability Over Temp. (μrad/°C)              | <8                               |
| Warm-up time (minutes)                               | <5                               |
| Beam height from base plate (mm)                     | 19                               |
| Power Consumption(W)                                 | <6                               |
| Fiber  | Multimode/ Single Mode           |
| Shock Tolerance(6ms)                                 | 7g laterally,15g vertically      |
| Power Supply   | 5V DC (Photoelectric integrated) |
| Operating temperature (°C)                           | 10-35                            |
| Storage temperature (°C)                             | -5-50                            |
| Modulation   | Modulation isn't available.      |
| Expected lifetime (hours)                            | 10000                            |
| Warranty   | 1 year                           |



This device complies with 21 CFR1040.10 and 1040.11  
Changchun New Industries Optoelectronics Tech. Co., Ltd. (CNI)  
888 JinHu Road, High-tech Zone Changchun, China

| MSL-DS-532  |  |   |
|---|--|---|
| Without Fiber   | With Multimode Fiber   | With Single Mode Fiber                                      |
| <br><br><br>100 (L) × 60 (W) × 40(H) mm <sup>3</sup> , 0.41kg | <br><br><br>130.5(L) × 60(W) × 45(H) mm <sup>3</sup> , 0.5kg | <br><br><br>139(L) × 60(W) × 46(H) mm <sup>3</sup> , 0.52kg |