



MDL-MD-637/640/642/500-1300mW



RED DIODE LASER
AT 637/640/642nm

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Central wavelength (nm)	637±5/ 640±5/ 642±5
Operating mode	CW
Output power (mW)	>500, 600, ..., 1300
Power stability (rms, over 4 hours)	<1%, <2%, <3%
Polarization direction	Horizontal/ Vertical
Beam diameter at the aperture (mm)	5.1×4.1
Beam divergence, full angle (mrad)	<1.0
Warm-up time (minutes)	<5
Operating temperature (°C)	10~35
Power supply (100-240VAC)	PSU-H-LED/ PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional
Expected lifetime (hours)	10000
Warranty	1 year



MDL-MD-637/640/642	PSU-H-LED	PSU-H-FDA
<p>153(L)×81(W)×93.7(H) mm³, 1.8kg</p>	<p>277 (L)×145(W)×106(H) mm³, 2.3kg</p>	<p>275 (L)×145(W)×104(H) mm³, 2.1kg</p>