

OEM-I-589 /1~700mW



LD PUMPED ALL-SOLID-STATE YELLOW LASER AT 589nm

All solid state laser at 589nm is made features of ultra compact, long lifetime and easy operating, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



SPECIFICATIONS


Wavelength (nm)	589±2	
Operating mode	CW	
Output power (mW)	>1, 100, ..., 700	
Power stability (rms, over 4 hours) at 25℃	<3%, <5%	
Transverse mode	Near TEM ₀₀	
Beam divergence, full angle (mrad)	~2.5	
Beam diameter at the aperture (mm)	~2.5	
Warm-up time (minutes)	<10	
Beam height from base plate (mm)	25 (OEM-I-589)	96 (I-589-HS)
Driver (12VDC 25A, power supply optional)	PSU-OEM-I	PSU-I-HS
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional	
Expected lifetime (hours)	10000	
Warranty period	1 year	

Note: The laser needs to be used on a heat sink with good heat dissipation.




OEM-I-589

Laser head




PSU-OEM-I (Driver)



I-589-HS

Laser head



PSU-I-HS (Driver)

