FS-F-515A/1-2W

FEMTOSECOND PULSED LASER AT 515nm




All Fiber Femtosecond pulsed laser at 515nm is made features of short pulse duration, high repetition rate, high stability and good beam quality, which is used in optical microscope, photon imaging, physics experiment, etc.

SPECIFICATIONS

Wavelength (nm)	515±5
Operating mode	Pulsed
Average power (W) [1]	1-2
Single pulse energy (uJ)	1-2
Rep. rate (MHz)	1
Pulse duration (fs)	<300
Peak power (MW)	1-6.7
Ave power stability (rms, 4 hours±3℃)	<2%, <1%
Warm-up time (minutes)	<10
Transverse mode	TEM_{00}
Beam divergence, full angle (mrad)	<1.0
Beam diameter at the aperture ($1/e^2$,mm)	<2
M^2 factor	<1.3
Beam height from base plate (mm)	118
Cooled method	Water cooled
Operating temperature (℃)	10-35
Power supply (100-240VAC)	RAD1PS
Expected lifetime (hours)	>10000





LASER HEAD (DRIVER Integrated)	POWER SUPPLY	WATER CHILLER
		
628 (L)×422 (W) ×145(H) mm³,40kg	**410 (L) ×483.5 (W) ×110.5 (H) mm³,4.5 kg**	**370 (L) ×258 (W) ×241 (H) mm³,12kg**

1 One fixed value between 1-2W.

Kokyo
株式会社 光響
Email : gs-inquiry@symphotony.com
Web : https://www.symphotony.com/